



**Brand** : SECURA  
**Model** : SX30-1416AJ  
**Product Name** : 1/4 Inch IR Array Led Bullet Camera

#### **Features**

- 1/4" DIS Sensor
- 700TV Lines, 0.1lux/F1.2, 0Lux (IR ON)
- 6mm Lens
- IR Effective Distance: 30~35M

#### **Specifications**

- IP Rating: IP66
- Type: IR Array Led Bullet Camera
- Signal System: PAL
- Pick Up Device: 1/4" DIS Sensor
- Picture Elements: 720(H)\*576(V)
- Resolution: 700TV Lines
- Min Illumination (Lux): 0.1lux/F1.2, 0Lux (IR ON)
- Vertical Frequency: 50/60 fields/sec
- Horizontal Frequency: 50/60 fields/sec
- Clock Frequency: 27MHz

- Scanning System: Progressive Scanning
- S/N Ratio: > 46dB
- Electronic Shutter: N/O
- Lens: 6mm Lens
- White Balance: Auto
- BLC : Auto
- Auto Gain Control: Auto
- GAMMA: R=2.2
- Video Output: 1.0Vp-p/75Ω
- Power Supply: DC12V±10%
- Current Consumption: <0.72W
- IR Effect Distance: 30~35M
- Dimension: 158\*100\*72MM
- Storage Temperature: -20°C~±70°C
- Operating Temperature: -20°C~±70°C



**Brand** : SECURA  
**Model** : SXD-1416AJ  
**Product Name** : 1/4 Inch IR Array Led Dome Camera  
**Features**  
1/4" DIS Sensor  
700TV Lines, 0.1lux/F1.2, 0Lux (IR ON)

### 3.6mm Lens

IR Effective Distance: 20M

#### Specifications

- IP Rating: IP66
- Type: IR Array Led Dome Camera
- Signal System: PAL
- Pick Up Device: 1/4" DIS Sensor
- Picture Elements: 720(H)\*576(V)
- Resolution: 700TV Lines
- Min Illumination (Lux): 0.1lux/F1.2, 0Lux (IR ON)
- Vertical Frequency: 50/60 fields/sec
- Horizontal Frequency: 50/60 fields/sec
- Clock Frequency: 27MHz
- Scanning System: Progressive Scanning
- S/N Ratio: > 46dB
- Electronic Shutter: N/O
- Lens: 3.6mm Lens
- White Balance: Auto
- BLC : Auto
- Auto Gain Control: Auto
- GAMMA: R=2.2
- Video Output: 1.0Vp-p/75Ω
- Power Supply: DC12V±10%
- Current Consumption: <0.65W
- IR Effect Distance: 20M
- Dimension: 99.97\*89MM
- Storage Temperature: -20°C~±70°C
- Operating Temperature: -20°C~±70°C